


TRANSISTOR (NPN)

FEATURES


- High Collector Current.
- Complementary to S9012.
- Excellent hFE Linearity.

SOT-23



1. BASE
2. EMITTER
3. COLLECTOR

CIRCUIT DIAGRAM



MARKING : J3





MAXIMUM RATINGS (Ta=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V _{CB0}	40	V
Collector-Emitter Voltage	V _{CEO}	20	V
Emitter-Base Voltage	V _{EB0}	5	V
Collector Current	I _{CM}	0.5	A
Power Dissipation	P _D	0.625	W
Junction Temperature	T _J	150	°C
Storage Temperature	T _{stg}	-55~150	°C


ELECTRICAL CHARACTERISTICS (Ta=25°C unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Max	Unit
Emitter-base breakdown voltage	V_{EBO}	$I_E=100\mu A, I_C=0$	5		V
Collector-base breakdown voltage	V_{CBO}	$I_C=100\mu A, I_E=0$	40		V
Collector-emitter breakdown voltage	V_{CEO}	$I_C=100\mu A, I_B=0$	20		V
Emitter cut-off current	I_{EBO}	$V_{EB}=5V, I_C=0$		0.1	μA
Collector cut-off current	I_{CBO}	$V_{CB}=40V, I_E=0$		0.1	μA
Collector cut-off current	I_{CEO}	$V_{CE}=20V, I_B=0$		0.1	μA
Collector-emitter saturation voltage	V_{CESAT}	$I_C=500mA, I_B=50mA$		0.6	V
Base-emitter saturation voltage	V_{BESAT}	$I_C=500mA, I_B=50mA$		1.2	V
DC current gain	h_{fe}	$V_{CE}=1V, I_C=50mA$	200	350	
Transition frequency	f_T	$V_{CE}=6V, I_C=20mA$ $F=30MHZ$	150		MHZ

TYPICAL CHARACTERISTICS



SOT-23 PACKAGE OUTLINE DRAWING



SYMBOL	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	0.900	1.15	0.035	0.045
A1	0.000	0.125	0.000	0.005
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF (0.4-0.6)		0.022REF (0.016-0.024)	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°